

FIRE DOOR COMPLIANCE VERIFICATION

This information sheet must be completed in full to obtain certification.

Project

.....

Project address

.....

Merchant Supplier

.....

Builders name

.....

Address

.....

Contact phone

.....

WALL

MASONRY  
STUD FRAME

STUD MATERIAL .....  
STUD SIZE .....  
WALL SHEETING .....

DOOR FRAME

INSTALLED IN ACCORDANCE WITH FIRE DOOR APPROVALS  
51 x 25 REBATE  
41 X 25 REBATE  
Frame Backfilled  
1.6mm Metal Frame Used

DOOR CLEARANCES

TOP & SIDES MAXIMUM 3mm  
BOTTOM MAXIMUM 15mm MINIMUM 3mm

FIRE RATING

-/60/30 (1 HOUR) QUANTITY .....  
-/120/30 (2 HOUR) QUANTITY .....  
-/180/30 (3 HOUR) QUANTITY .....  
-/240/30 (4 HOUR) QUANTITY .....

HARDWARE

MANUFACTURER & MODEL NUMBER MUST BE SPECIFIED

LOCKSET/LATCHSET .....  
OTHER .....  
LATCHBACKSET .....  
DOOR CLOSER .....  
CLOSER BACKCHECK .....

PAIRS OF DOORS

HEADLATCH .....

- AUTOFLUSH BOLTS .....
- SEQUENCE SELECTOR .....
- ALUMINIUM MEETING .....

STILES.....

**ONLY FIRE TESTED AND APPROVED HARDWARE CAN BE FITTED TO FIRE DOORS.**

OPERATION  DOOR CLOSED TO FULLY LATCHED POSITION - DOOR MUST LATCH FULLY UNASSISTED

I ..... the undersigned, declare that the above information is true and correct.

The fire door assembly must comply with as/nzs 1905.1:2015 before certification can be issued.

SIGNED..... DATE ..... ON BEHALF OF.....